

USG BORAL SHEETROCK® LIGHTWEIGHT ALL-PURPOSE JOINT COMPOUND



USG Boral SHEETROCK® lightweight all-purpose joint compound is more flexible and easier than other joint compounds for embedding joint tape and for filling and finishing gypsum panel joints, corner bead, trim and fasteners. Also for hand-applying simple textures. Complies with ASTM C475.

PRODUCT FEATURES

For professional drywall finishing

- High performance compound. • Minimizes cratering.
- Excellent workability (including better slip and pull).
- Low shrinkage, easy sanding. • Better filling



1st Coat



2nd Coat



Finishing Coat



Hand and Mechanical Tool



Patching



Skimming



Sandable

PRODUCT INFORMATION

Color	White
Drying Time	12-24 hours (depending on local conditions)
Packaging	17 Liters re-sealable pail
VOC content	<30g/L
Skimming Coverage	33m ² (based on 1mm thickness)

ADVANTAGES

USG SHEETROCK Brand quality In addition to the cost-saving benefits described above, this vinyl-based compound offers all the advantages of high-quality SHEETROCK Brand Ready-Mixed Joint Compound.

Faster mixing time When additional water is necessary, SHEETROCK Brand Lightweight All Purpose Joint Compound accepts water

more quickly to reduce solution time and mixes with less effort than conventional compounds.

Better slip, excellent bond Provides superior ease of handling, good crack resistance and excellent adhesion. **More open time** Facilitates working back, even in fast-drying conditions, by providing more wet-edge life to prevent rolling and tearing of previously laid compound; also eliminates nuisance of crusted compound flaking from open container walls.

Low shrinkage for faster, finer finishing Factory-controlled low-shrinkage formulation allows finer finished work and usually requires only two coats over metal bead and fasteners, saving time and money.

Minimized cratering Special vacuum processing and patented formulation technology eliminate entrained air to minimize cratering and minor surface imperfections.

