

# USG BORAL ALL PURPOSE JOINT COMPOUND



USG BORAL ALL PURPOSE JOINT COMPOUND is an air-drying, compound suitable for all three coat applications or as a finishing coat for all plasterboard joints, angles and fastener heads. Complies with ASTM C475.

## PRODUCT FEATURES

- Premium grade, all purpose or finishing compound.
- Used for all three coats or as a skimming coat.
- Excellent workability, easy application by hand or with mechanical tools.
- Minimal mixing & cleaning of tools.
- Can be sanded by hand or with mechanical sanding tools.
- Excellent surface for painting.



1st Coat



2nd Coat



Finishing Coat



Hand and Mechanical Tool



Patching



Skimming



Sandable

## PRODUCT INFORMATION

<b>Color</b>	White
<b>Working Time</b>	Drying Type: Minimum 24 hours drying time or longer in adverse climatic conditions
<b>Packaging</b>	25kg
<b>VOC content</b>	<50g/L
<b>Tapping &amp; Filling Coverage</b>	50m <sup>2</sup>

## APPLICATION

- Surfaces must be clean and free from dust.
- USG Boral All Purpose Joint Compound may be diluted to a workable viscosity by adding water followed by mechanical mixing if desired.
- Can be applied by hand or mechanical tools.
- When using USG Boral All Purpose Joint Compound for all three coats, the first coat must be used to bed a high-quality paper tape.
- USG Boral All Purpose Joint Compound must be allowed to dry thoroughly (up to 24 hours depending on temperature & humidity) before re-coating or sanding.
- Only apply over setting type compounds that have been allowed to dry thoroughly.
- Sand with care using 180 or 220 grit paper.
- Thoroughly clean all tools and equipment after use.

