

USG BORAL SHEETROCK® ALL PURPOSE JOINT COMPOUND



USG Boral SHEETROCK® ALL PURPOSE joint compound is an air-drying, compound suitable for all three coat applications or as a finishing coat for all plasterboard joints, angles and fastener heads. Complies with ASTM C475.

PRODUCT FEATURES

- Premium grade, all purpose or finishing compound.
- Used for all three coats or as a skimming coat.
- Excellent workability, easy application by hand or with mechanical tools.
- Minimal mixing & cleaning of tools.
- Can be sanded by hand or with mechanical sanding tools.
- Excellent surface for painting.



1st Coat



2nd Coat



Finishing Coat



Hand and Mechanical Tool



Patching



Skimming



Sandable

PRODUCT INFORMATION

Color	White
Working Time	Drying Type: Minimum 24 hours drying time or longer in adverse climatic conditions
Packaging	Net 5 kg, 15 Kg and 28 kg re-sealable pail
VOC content	<50g/L
Tapping & Filling Coverage	56m ²

APPLICATION

- Surfaces must be clean and free from dust.
- USG Boral SHEETROCK® All Purpose may be diluted to a workable viscosity by adding water followed by mechanical mixing if desired.
- Can be applied by hand or mechanical tools.
- When using USG Boral SHEETROCK® All Purpose for all three coats, the first coat must be used to bed a high-quality paper tape.
- USG Boral SHEETROCK® All Purpose compound must be allowed to dry thoroughly (up to 24 hours depending on temperature & humidity) before re-coating or sanding.
- Only apply over setting type compounds that have been allowed to dry thoroughly.
- Sand with care using 180 or 220 grit paper.
- Thoroughly clean all tools and equipment after use.

